

HVI LI 20 L6M SR2875 FSP1000 DSH GFK AL (819 243)



Figure without obligation

Type	HVI LI 20 L6M SR2875 FSP1000 DSH GFK AL
Part No.	819 243
Material of supporting tube	GRP / Al
Length of supporting tube	2875 mm
Material of air-termination tip	StSt
Length of air-termination tip	1000 mm
Outside diameter Ø GRP	30 mm
Diameter Ø of conductor	20 mm
Colour of conductor	grey •
Material of conductor	Cu
Coluor RAL	similar 7000
Cross section of core	19 mm²
Lightning current carrying capability (class / I _{imp})	H1 / 150 kA
Equivalent separation distance s (in air)	≤ 45 cm
Material of insulation	PE
Material of sheath	PE
Characteristics of sheath	UV stabilised and weather resistant
Connection diameter	10 mm
EB connection conductor	strip StSt 18 x 0.4 mm
Material of connection elements	StSt
Material of EB connection element	StSt
Minimum order length	6 m
Max. gust wind speed	149 km/h
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	7,93 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364255951
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.