


APC 60 62 (785 758)



Figure without obligation

Figure without obligation

Find the right size to get the perfect fit with your DEHNcare personal protective equipment.



DEHNcare ArcClassic jacket and trousers											DEHNcare ArcClassic coat													
Standard men's sizes (cm)																								
Ordering size	46	48	50	52	54	56	58	60	62	64	66	68	70	72	74	76	78	80	82	84	86	88	90	
Body size	145-177	148-180	151-183	154-186	157-189	160-192	163-195	166-198	169-201	172-204	175-207	178-210	181-213	184-216	187-219	190-222	193-225	196-228	199-231	202-234	205-237	208-240	211-243	214-246
Chest measurement	92-95	96-100	101-103	104-107	108-111	112-115	116-119	120-123	124-127	128-131	132-135	136-139	140-143	144-147	148-151	152-155	156-159	160-163	164-167	168-171	172-175	176-179	180-183	184-187
Waistband	79-82	82-86	87-90	91-94	95-98	99-102	103-107	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Hip size	104	106	108	110	112	114	116	118	120	122	124	126	128	130	132	134	136	138	140	142	144	146	148	150
Inside leg length	83.5	84.5	85.5	86	86.5	87	87.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Sleeve length	69.6	70.2	70.8	71.4	72	72.6	73.2	73.8	74.4	75	75.6	76.2	76.8	77.4	78	78.6	79.2	79.8	80.4	81	81.6	82.2	82.8	83.4

- Reinforced stand-up collar
- Zip and hook-and-loop fasteners

Type	APC 60 62
Part No.	785 758
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy (W_{arc} or W_{LEP})	320 kJ
Extended electric arc energy (W_{arc} or W_{LEP}) (based on box test)	630 kJ
EuroTest PIP001 (10 kA / 1 s – three-pole)	Yes
Arc Rating – ATPV (Open Arc Test)	33.1 cal / cm ²
PPE category (NFPA 70E)	PPE 3
Size (international)	60 / 62 (XXL)
Outer material	Siliconised calf grain leather, 100% Kevlar interlock knit
Inner material	100% cotton
Material (sewing thread)	100% Kevlar
Standard	IEC 61482-2, EN ISO 14116
Weight	3,21 kg
Customs tariff number (Comb. Nomenclature EU)	42031000
GTIN	4013364245150
PU	1 pc(s)

In case of very heavy soiling, the protective coat can be dry cleaned by a specialist leather cleaner.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.