


## SR D50 3500 FS2500 IA SA HVIP GFK AL (105 543)



Figure without obligation



Supporting tube with internal sealing end and EB spring element. Air-termination rod  $\varnothing 22 / 16 / 10$  mm.

Type	SR D50 3500 FS2500 IA SA HVIP GFK AL
Part No.	105 543
Material of air-termination rod	Al
Length of air-termination rod	2500 mm
Material of supporting tube	GRP / Al
Length of supporting tube	3500 mm
Outside diameter $\varnothing$	50 mm
Transport length	3500 mm
Wall thickness	4 mm
Material factor km	0.7
Length of insulating clearance	1800 mm
Permanent temperature range	-50 °C ... +100 °C
Type	UV-stabilised
Sleeve	60 x 5 mm
Suitable for installation outside the tube	yes
Pull-out force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Bending force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	6,24 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364271845
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.