


SR D50 4700 FSP1000 IP HVI GFK AL (105 332)



Figure without obligation



Supporting tube with internal sealing end and EB spring element. Air-termination tip Ø10 mm.

| Type | SR D50 4700 FSP1000 IP HVI GFK AL |
|---|--|
| Part No. | 105 332 |
| Material of air-termination tip | StSt |
| Length of air-termination tip | 1000 mm |
| Material of supporting tube | GRP / Al |
| Length of supporting tube | 4700 mm |
| Transport length | 4700 mm |
| Outside diameter Ø | 50 mm |
| Length of insulating clearance | 1535 mm |
| Wall thickness | 4 mm |
| Material factor km | 0.7 |
| Permanent temperature range | -50 °C ... +100 °C |
| Type | UV-stabilised |
| Sleeve | 60 x 5 mm |
| Max. free length with air-termination tip (wall mounting) | 4000 mm |
| Max. gust wind speed | (Max. free length 4,000 mm, 1x HVI inside) 237 km/h |
| Max. gust wind speed | (Max. free length 4,000 mm, 1x HVI outside) 184 km/h |
| Max. gust wind speed | (Max. free length 4,000 mm, 4x HVI outside) 149 km/h |
| Pull-out force with a length of 500#mm | 200 N (supporting tube insulator as per 62561-8) |
| Bending force with a length of 500#mm | 200 N (supporting tube insulator as per 62561-8) |
| Standard | DIN IEC/TS 62561-8 (VDE V 0185-561-8) |
| Weight | 8,25 kg |
| Customs tariff number (Comb. Nomenclature EU) | 85389099 |
| GTIN | 4013364152519 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.