


DGP C S (952 030)


- Specifically designed for use in "3+1" and "1+1" circuits of TT systems according to IEC 60364-5-53 between neutral conductor N and protective conductor PE
- High discharge capacity
- Two-part surge arrester consisting of a base part and plug-in spark-gap based protection module



Figure without obligation



Basic circuit diagram DGP C S



Dimension drawing DGP C S

N-PE surge arrester; FM version with floating remote signalling contact.

Type	DGP C S
Part No.	952 030
SPD according to EN 61643-11 / IEC 61643-11	type 2 / class II
Energy coordination with terminal equipment (≤ 10 m)	type 2 + type 3
Max. continuous operating voltage (a.c.) (U_c)	255V (50 / 60 Hz)
Nominal discharge current (8/20 μ s) (I_n)	20 kA
Max. discharge current (8/20 μ s) (I_{max})	40 kA
Follow current extinguishing capability (I_f)	100 A _{rms}
Lightning impulse current (10/350 μ s) (I_{imp})	12 kA
Voltage protection level (U_p)	≤ 1.5 kV
Response time (t_A)	≤ 100 ns
Temporary overvoltage (TOV) (U_T) – Characteristic	1200 V / 200 ms – withstand
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm ² solid / flexible
Cross-sectional area (max.)	35 mm ² stranded / 25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	1 module(s), DIN 43880
Approvals	KEMA, VDE, UL

Arrester use at 16.7 Hz – traction power supply systems

Type	DGP C S
Part No.	952 030
– Test voltage AC (U_c)	255 V
– Nominal frequency AC (f_N)	16.7 Hz
Weight	111 g
Customs tariff number (Comb. Nomenclature EU)	85363030
GTIN	4013364108530
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.