


DSO 1 255 (900 230)


- Coordinated spark-gap-based lightning current arrester
- Extremely high lightning current discharge capacity up to 200 kA (10/350 μ s)
- Low voltage protection level $U_p \leq 2.5$ kV



Figure without obligation



Basic circuit diagram DSO 1 255



Dimension drawing DSO 1 255

Coordinated, single-pole lightning current arrester for installation on busbars or mounting plates.

Type	DSO 1 255
Part No.	900 230
Classification according to EN 61643-11 / IEC 61643-11	type 1 / class I
Max. continuous operating voltage (a.c.) (U_c)	255 V (50 / 60 Hz)
Lightning impulse current (10/350 μ s) (I_{imp})	200 kA
Specific energy (W/R)	10 MJ/ohms
Voltage protection level (U_p)	≤ 2.5 kV
Directly coordinated with DEHNguard (cable length ≥ 35 cm)	DG S 440 (FM)
Follow current extinguishing capability (a.c.) (I_n)	3 kA _{rms}
Follow current limitation / Selectivity	No tripping of fuses up to 3 kA(prosp.)
Response time (t_d)	≤ 100 ns
Max. mains-side overcurrent protection	160 A gG
Short-circuit withstand capability	3 kA _{rms}
Temporary overvoltage (TOV) (U_T) – Characteristic	440 V / 120 min. – withstand
Operating temperature range (T_U)	-40 °C ... +80 °C
Number of ports	1
For mounting on	PE(N) busbars, min. 35 mm ²
Connection	via cable lug, min. 35 mm ² / max. 50 mm ²
Enclosure material	thermoplastic, red, UL 94 V-2
Place of installation	indoor installation
Weight	1,49 kg
Customs tariff number (Comb. Nomenclature EU)	85363090
GTIN	4013364153783
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.