


HVI LI PL L6M SR1600 FSP500 GFK AL V2A (819 672)



Figure without obligation



With internal sealing end and air-termination tip, StSt, Ø10 mm, length 500 mm.

| Type | HVI LI PL L6M SR1600 FSP500 GFK AL V2A |
|---|--|
| Part No. | 819 672 |
| Material of air-termination tip | StSt |
| Length of air-termination tip | 500 mm |
| Material of supporting tube | GRP / Al |
| Length of supporting tube | 1600 mm |
| Transport length | 1600 mm |
| Outside diameter Ø | 40 mm |
| Diameter Ø conductor | 21 mm |
| Colour of conductor | grey |
| Material of conductor | Cu |
| RAL colour | similar to 7004 |
| Cross-section of core (solid) | 16 mm ² |
| Lightning current carrying capability (class / I _{imp}) | H1 / 150 kA |
| Equivalent separation distance s (in air) | ≤ 60 cm |
| Material of insulation | PE |
| Material of sheath | PE |
| Material characteristics | UV stabilised and weather resistant |
| Connection diameter | 10 mm |
| Material of connection elements | StSt |
| Supporting tube | 40 x 4 mm |
| Minimum order length | 6 m |
| Pull-out force with a length of 500#mm | 200 N (supporting tube insulator as per 62561-8) |
| Bending force with a length of 500#mm | 200 N (supporting tube insulator as per 62561-8) |
| Standard | DIN IEC/TS 62561-8 (VDE V 0185-561-8) |
| Weight | 7,07 kg |
| Customs tariff number (Comb. Nomenclature EU) | 85389099 |
| GTIN | 4013364494527 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Specifications regarding max. gust wind speeds of the air-termination systems can be found in the wind load matrix.