


DSH ZP 2 TT 255 (909 531)


- Type 1 + type 2 + type 3 combined arrester based on spark gap technology, meets the minimum requirements of IEC 60364-5-53 clause 534 for the nominal discharge current capacity I_n and the lightning current discharge capacity I_{imp} according to class of LPS III + IV in residential buildings
- Easy, fast and completely toolless installation by snapping the arrester on 40 mm busbar systems
- Capable of protecting terminal equipment
- Small width of only 38 mm allows DEHNshield ZP to be combined with a supply adapter and thus installation between two selective main circuit breakers in a single meter panel
- A suitable cover clip according to DIN VDE 0603-1 for every standard meter panel is included in delivery



Figure without obligation



Basic circuit diagram DSH ZP 2 TT 255



Dimension drawing DSH ZP 2 TT 255

Combined arrester for TT and TN-S systems for use in main power supply systems (3+1 configuration) of residential buildings with external lightning protection (class of LPS III/IV).

Type	DSH ZP 2 TT 255
Part No.	909 531
SPD according to EN 61643-11 / IEC 61643-11	type 1 + type 2 + type 3 / class I + class II + class III
Energy coordination with terminal equipment (≤ 10 m)	type 1 + type 2 + type 3
Nominal voltage (a.c.) (U_n)	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) (U_c)	255 V (50 / 60 Hz)
Lightning impulse current (10/350 μ s) [L1+L2+L3+N-PE] (I_{total})	50 kA
Lightning impulse current (10/350 μ s) [L-N] (I_{imp})	12.5 kA
Specific energy [L-N] (W/R)	39.06 kJ/ohms
Lightning impulse current (10/350 μ s) [N-PE] (I_{imp})	50 kA
Specific energy [N-PE] (W/R)	625 kJ/Ohm
Nominal discharge current (8/20 μ s) [L-N]/[N-PE] (I_n)	20 / 80 kA
Voltage protection level [L-N] (U_p)	≤ 1.5 kV
Voltage protection level [N-PE] (U_p)	≤ 1.5 kV
Open-circuit voltage of the combination wave generator (U_{oc})	20 kV
Follow current extinguishing capability [L-N] (a.c.) (I_{fi})	25 kA _{rms}
Follow current extinguishing capability [N-PE] (a.c.) (I_{fi})	100 A _{rms}
Follow current limitation / Selectivity	no tripping of a 32 A gG fuse up to 25 kArms (prosp.)
Max. mains-side overcurrent protection	160 A gG
Temporary overvoltage (TOV) [L-N] (U_T) – Characteristic	440 V / 120 min. – withstand
Temporary overvoltage (TOV) [N-PE] (U_T) – Characteristic	1200 V / 200 ms – withstand
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (PEN, $\frac{1}{2}$)	16-25 mm ² stranded, fine-stranded
For mounting on	40 mm busbar systems
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 30 (in combination with cover)
Approvals	VDE
Extended technical data:	-----
Protection level [L-PE] (U_p)	≤ 1.6 kV
Weight	519 g
Customs tariff number (Comb. Nomenclature EU)	85363090
GTIN	4013364424807
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.