


**DSH ZP B2 TNC 255 (909 330)**


- Type 1 + type 2 + type 3 combined arrester based on spark gap technology, meets the minimum requirements of IEC 60364-5-53 clause 534 for the nominal discharge current capacity  $I_n$  and the lightning current discharge capacity  $I_{imp}$  in case of overhead line supply
- Easy, fast and completely toolless installation by snapping the arrester on 40 mm busbar systems
- Capable of protecting terminal equipment
- Small width of only 38 mm allows DEHNshield ZP to be combined with a supply adapter and thus installation between two selective main circuit breakers in a single meter panel
- A suitable cover clip according to DIN VDE 0603-1 for every standard meter panel is included in delivery



Figure without obligation



Basic circuit diagram DSH ZP B2 TNC 255



Dimension drawing DSH ZP B2 TNC 255

Combined arrester for TN-C systems for use in the main power supply system (3+0 configuration) of residential buildings without external lightning protection (also with overhead line supply).

Type	DSH ZP B2 TNC 255
Part No.	909 330
SPD according to EN 61643-11 / IEC 61643-11	type 1 + type 2 + type 3 / class I + class II + class III
Energy coordination with terminal equipment ( $\leq 10$ m)	type 1 + type 2 + type 3
Nominal voltage (a.c.) ( $U_N$ )	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) ( $U_C$ )	255 V (50 / 60 Hz)
Lightning impulse current (10/350 $\mu$ s) [L1+L2+L3-PEN] ( $I_{total}$ )	22.5 kA
Lightning impulse current (10/350 $\mu$ s) [L-PEN] ( $I_{imp}$ )	7.5 kA
Specific energy [L-PEN] (W/R)	14.06 kJ/ohms
Nominal discharge current (8/20 $\mu$ s) [L-PEN]/[L1+L2+L3-PEN] ( $I_n$ )	20 / 60 kA
Voltage protection level ( $U_P$ )	$\leq 1.5$ kV
Open-circuit voltage of the combination wave generator ( $U_{oc}$ )	20 kV
Follow current extinguishing capability (a.c.) ( $I_{fi}$ )	25 kA <sub>rms</sub>
Follow current limitation / Selectivity	no tripping of a 32 A gG fuse up to 25 kA <sub>rms</sub> (prosp.)
Max. mains-side overcurrent protection	160 A gG
Temporary overvoltage (TOV) [L-N] ( $U_T$ ) – Characteristic	440 V / 120 min. – withstand
Operating temperature range ( $T_U$ )	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (PEN, $\pm$ )	16-25 mm <sup>2</sup> stranded, fine-stranded
For mounting on	40 mm busbar systems
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 30 (in combination with cover)
Approvals	VDE
Weight	431 g
Customs tariff number (Comb. Nomenclature EU)	85363090
GTIN	4013364424852
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.