


**BCO CL2 BD EX 24 (927 984)**


- LifeCheck arrester monitoring and integrated status indication
- Compact two-pole arrester for optimal protection of one pair in intrinsically safe signal circuits
- For installation in conformity with the lightning protection zone concept at the boundaries from  $O_A - 2$  and higher



Figure without obligation



Basic circuit diagram BCO CL2 BD EX 24



Dimension drawing BCO CL2 BD EX 24

Space-saving, compact surge arrester with a width of 6 mm and push-in connection technology with status indication for protecting one pair of intrinsically safe measuring circuits and bus systems, meets FISCO requirements. Insulation strength > 500 V line-ground.

Type	BCO CL2 BD EX 24
Part No.	927 984
SPD class	<b>TYPE 4</b> P2
Impulse category	D1, C1, C2, C3, B2
Nominal voltage ( $U_n$ )	24 V
Max. continuous operating voltage (d.c.) ( $U_c$ )	36 V
Max. continuous operating voltage (a.c.) ( $U_c$ )	25.4 V
Nominal current at 80 °C ( $I_n$ )	0.5 A
D1 Total lightning impulse current (10/350 $\mu$ s) ( $I_{imp}$ )	3 kA
D1 Lightning impulse current (10/350 $\mu$ s) per line ( $I_{imp}$ )	1.5 kA
C2 Total nominal discharge current (8/20 $\mu$ s) ( $I_n$ )	10 kA
C2 Nominal discharge current (8/20 $\mu$ s) per line ( $I_n$ )	5 kA
Voltage protection line-line for $I_n$ C2 ( $U_P$ )	$\leq 65$ V
Voltage protection level line-PG for $I_n$ C2 ( $U_P$ )	$\leq 1100$ V
Voltage protection level line-line for 1 kV/ $\mu$ s C3 ( $U_P$ )	$\leq 48$ V
Voltage protection level line-PG for 1 kV/ $\mu$ s C3 ( $U_P$ )	$\leq 1000$ V
Series resistance per line	1 ohms
Cut-off frequency line-line ( $f_c$ )	3.5 MHz
Capacitance line-line (C)	$\leq 2$ nF
Capacitance line-PG (C)	$\leq 15$ pF
Operating temperature range ( $T_U$ )	-40 °C ... +80 °C
Operating state / fault indication	green / red
Degree of protection	IP 20
For mounting on	35 mm DIN rails acc. to EN 60715
Connection (input / output)	push-in / push-in
Cross-sectional area, solid	0.2-2.5 mm <sup>2</sup>
Cross-sectional area, flexible	0.2-2.5 mm <sup>2</sup>
Earthing via	35 mm DIN rails acc. to EN 60715
Enclosure material	polyamide PA 6.6
Colour	blue
Test standards	IEC 61643-21 / EN 61643-21
Approvals	ATEX, IECEx, CCC, SIL
SIL classification	up to SIL3 <sup>1)</sup>
ATEX approvals (1)	TÜV 19 ATEX 8476 X: II (1)2 G Ex ia [ia Ga] IIC T4 ... T6 Gb
ATEX approvals (2)	TÜV 19 ATEX 8476 X: II 2 G Ex ib IIC T4 ... T6 Gb
ATEX approvals (3)	TÜV 19 ATEX 8476 X: II (1) D [Ex ia Da] IIIC
IECEX approvals (1)	IECEX TUR 20.0025X: Ex ia [ia Ga] IIC T4 ... T6 Gb
IECEX approvals (2)	IECEX TUR 20.0025X: Ex ib IIC T4 ... T6 Gb
IECEX approvals (3)	IECEX TUR 20.0025X: [Ex ia Da] IIIC
China Compulsory Certification	CCC No. 2021312304001130 (Ex ia, Ex ib)
Extended technical data:	-----
- Max. discharge current (8/20 $\mu$ s) [1/2 - PG], [1+2 - PG] ( $I_{max}$ )	20 kA
- Discharge current (8/20 $\mu$ s) [1/2 - PG], [1+2 - PG]	10 kA (10x)
- Voltage protection level line-PG at 1 kV/ $\mu$ s C3 after being subjected to $I_{max}$ ( $U_P$ )	$\leq 1000$ V
Weight	33 g
Customs tariff number (Comb. Nomenclature EU)	85363010
GTIN	4013364412002

# Product Data Sheet: BLITZDUCTORconnect – Compact



Type	BCO CL2 BD EX 24
Part No.	927 984
PU	1 pc(s)

<sup>1)</sup> For details, see: [www.dehn-international.com](http://www.dehn-international.com)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.