

NEW APT ID F 54 (787 690)



Figure without obligation

Find the right size to get the perfect fit with your DEHNcare personal protective equipment



DEHNcare ArcFit Indoor / Outdoor

Optimal measurements

Measurement	XS	S	M	L	XL	XXL	XXXL
Body height	165	170	175	180	185	190	195
Body weight	60	70	80	90	100	110	120
Waist circumference	75	80	85	90	95	100	105
Hip circumference	85	90	95	100	105	110	115
Waist to hip length	75	78	81	84	87	90	93
Waist to ankle length	90	93	96	99	102	105	108
Waist to knee length	55	58	61	64	67	70	73
Waist to heel length	100	103	106	109	112	115	118
Waist to ankle length	90	93	96	99	102	105	108
Waist to knee length	55	58	61	64	67	70	73
Waist to heel length	100	103	106	109	112	115	118

Optimal body measurements

Measurement	XS	S	M	L	XL	XXL	XXXL
Body height	165	170	175	180	185	190	195
Body weight	60	70	80	90	100	110	120
Waist circumference	75	80	85	90	95	100	105
Hip circumference	85	90	95	100	105	110	115
Waist to hip length	75	78	81	84	87	90	93
Waist to ankle length	90	93	96	99	102	105	108
Waist to knee length	55	58	61	64	67	70	73
Waist to heel length	100	103	106	109	112	115	118

Figure without obligation

Type	APT ID F 54
Part No.	787 690
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy (W_{arc} or W_{LEP})	320 kJ
Arc Rating – ATPV (Open Arc)	18 cal / cm ² *)
Arc Rating – ELIM (Open Arc)	13 cal / cm ²
PPE category (NFPA 70E)	PPE 2
Material	Cotton (52%), modacrylic (22%), viscose (19%), para-aramid (6%), static inhibitors (1%)
Weight per unit area	450 g/m ²
Material (sewing thread)	Kevlar (100%)
Standard	IEC 61482-2, EN ISO 11612, EN 1149-5, EN ISO 13688, EN ISO 11611, EN 17353
Primary colour	grey
Secondary colour	black
Zipper	red
Size (international)	54 (3XL/4XL)
Design code	TIGRBLRE0000P0
Weight	878 g
Customs tariff number (Comb. Nomenclature EU)	62034211
GTIN	4013364490789
PU	1 pc(s)

*) Outer fabric after preparation

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.