

HVI 23 L6M SR3200 SA RFS2500 AL DBS V2A (819 383)



Figure without obligation

With internal sealing end and air-termination rod Ø22 /16 / 10 mm.

With tripod (part no. 105 790).

Type	HVI 23 L6M SR3200 SA RFS2500 AL DBS V2A	
Part No.	819 383	
Material of air-termination rod	Al	
Length of air-termination rod	2500 mm	
Material of supporting tube	GRP / Al	
Length of supporting tube	3200 mm	
Transport length	3200 mm	
Outside diameter Ø	50 mm	
Diameter Ø conductor	23 mm	
Colour of conductor	grey	
Material of conductor	Cu	
RAL colour	similar to 7035	
Cross-section of core (stranded)	19 mm ²	
Lightning current carrying capability (class / I _{imp})	H1 / 150 kA	
Equivalent separation distance s (in air)	≤ 75 cm	
Material of insulation	PE	
Material of sheath	PE	
Material characteristics	UV-stabilised and weather resistant	
Connection diameter	10 mm	
Material of connection elements	StSt	
Supporting tube	50 x 4 mm	
Radius of tripod	680 mm	
Space required for tripod	1175 x 1020 mm	
Minimum order length	6 m	
Pull-out force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)	
Bending force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)	
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)	
Weight	19,1 kg	
Customs tariff number (Comb. Nomenclature EU)	85389099	
GTIN	4013364241961	
PU	1 pc(s)	

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

The conductor cannot be returned as it is made to order.