# NEW APT OD OG 106 (787 874)

Figure without obligation



Figure without obligation

| Type<br>Part No. | APT OD OG 106<br>787 874 |
|---|---|
| Arc fault protection class (box test 7 kA / 0.5 s – single-pole) | APC 2 |
| Arc energy ($W_{arc}$ or $W_{LBP}$) | 320 kJ |
| Arc rating – ATPV (open arc) | 16 cal / cm² *) |
| Arc rating – ELIM (open arc) | 13 cal / cm² |
| PPE category (NFPA 70E) | PPE 2 |
| Material | Modacrylic (40%), viscose (59%), static inhibitors (1%), PU membrane: meta-armid knitting (100%) |
| Weight per unit area | 330 g/m² |
| Material (sewing thread) | Kevlar (100%) |
| Standard | IEC 61482-2, EN ISO 11612, EN 1149-5, EN ISO 20471, EN 13034, EN ISO 13688, EN ISO 11611 |
| Primary colour | fluorescent orange |
| Secondary colour | grey |
| Zipper | red |
| Size (international) | 106 (L-L) |
| Design code | TOORGRRE0000P0 |
| Weight | 930 g |
| Customs tariff number (Comb. Nomenclature EU) | 62034911 |
| GTIN | 4013364492004 |
| PU | 1 pc(s) |

*) Outer fabric after preparation

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.