




AL ZF DUL 6.10 B5.2 6.5 L81 STTZN (377 201)



Figure without obligation



Arrangement:

Type	AL ZF DUL 6.10 B5.2 6.5 L81 STTZN
Part No.	377 201
Material of bracket	HDG steel
Material thickness (t1)	3 mm
Fixing	[4x] Ø5.2 / [2x] Ø6.5 mm
Fixing possibility	blind rivets or drilling screws
Application note	according to EN 62305-3 Suppl. 1 4 rivets Ø5mm, 2 rivets Ø6mm shall be used to connect materials ≥ 0.5mm thick or 2 Parker screws StSt Ø6.3mm for materials ≥ 2mm thick.
Material of double clamp	HDG steel
Screw	⬆ M10 x 30 mm
Material of screw / nut	HDG steel
Connection	lengthwise / crosswise
Connection with	double cleat
Clamping range Rd	8-10 mm
Lightning current carrying capability (10/350 µs)	50 kA ^{*)}
Standard	EN 62561-1
Weight	118 g
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364525122
PU	50 pc(s)

*) For exact assignment, see test certificate.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.