

## LIGHT SB FO E P CI WRU SRC 44 (787 228)



Figure without obligation

| Type  | LIGHT SB FO E P CI WRU SRC 44  |
|---|--|
| Part No.                                      | 787 228 <small>NEW</small>   |
| Standard                                      | EN ISO 20345:2011  |
| Size  | 44   |
| Material                                      | Leather  |
| Lining  | Textile  |
| Classification as per EN ISO 20345:2011       | Class I  |
| Protection class as per EN ISO 20345:2011     | SB   |
| Shoe shape                                    | B  |
| Protective cap                                | Plastic  |
| Sealed with                                   | Shoelaces  |
| Sole type                                     | Polyurethane   |
| Penetration protection                        | Composite textile material   |
| Metal-free equipment                          | Yes  |
| Colour  | Black / orange   |
| Application                                   | Electrical engineering   |
| Special properties                            | The outsole provides electrical insulation at voltages up to 1,000 V – M Ω > 1,000 if requirements are met (no moisture, does not refer to the upper shaft). Electrical resistance acc. Canadian standard CSA Z 195 14 Increase by 1 kV/s Voltage 20,000 V / 60 Hz duration of 1 minute. Electrical resistance acc. the ASTM 2413 -11 standard increase of 1 kV/sec Voltage 20,000 V / 60 Hz duration of 1 minute. Requirement of electric flow lower than 1.0 mA. |
| Weight  | 1 Pa/pc(s)   |
| Customs tariff number (Comb. Nomenclature EU) | 64039193   |
| GTIN  | 4013364508125  |
| PU  | 1 Pa   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.