

T2100 (578 322)



Figure without obligation

Can be used for earth loop measurement and for earthing measurement without an auxiliary earth electrode. Measurement category CAT IV / CAT III.

Automatic calibration, Bluetooth interface, including software.

Can be used as an accessory for the COMBI G3 installation test device.

Wide range of accessories:

Robust protective case

4x 1.5-V AA batteries

Resistance test loop 1 Ω, 5 Ω, 10 Ω

Operating instructions

ISO 9000 calibration certificate

Type	T2100
Part No.	578 322 <small>NEW</small>
Display	Digital LCD display with backlight
Battery	4x 1.5-V AA batteries
RS-232 interface	4800 baud
Compatible master device	COMBI G3
Resistance measuring range	0.01 to 1,200 Ω
Security	IEC/EN 61010-1; IEC/EN 61010-2-032
Degree of insulation/pollution	Double insulation / 2
Measurement category	CAT IV 400V, CAT III 600V to ground
Loop inductivity resolution	Optical / USB interface
Internal memory	99 measured values
Inner diameter of tongs	31 x 48 mm
Enclosure material	Plastic
Dimensions of tongs (l x w x d)	290 x 100 x 55 mm
Weight	1,93 kg
Customs tariff number (Comb. Nomenclature EU)	90303370
GTIN	4013364538665
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.