

## COMBI G3 (578 323)



Figure without obligation

VDE0100 / VDE 0105 installation test device  
Can be used for low-impedance, loop impedance and insulation measurement.

For testing the continuity of steel reinforcements in reinforced concrete with 10 A test current as per DIN EN 62305-3.  
(Necessary accessories: EQUITEST 10 A – part no. 578 321)

Additional measuring methods:  
Earthing measurement with 2 and 3-conductor method  
Earthing measurement with optional earth resistance clamp meter (tongs T2100 – part no. 578 322)  
Earth resistance measurement with 4-conductor method

Wide range of accessories:  
Robust transport case  
6 rechargeable batteries (NiMH 1.2 V AA)  
External charger  
Universal KIT: 4 measuring lines + 4 alligator clips + 3 test prods  
3-conductor Schuko cable (L 1,500 mm)  
Stylus  
Quick guide and operating instructions  
ISO9000 calibration certificate  
TOPVIEW software + USB connecting cable

Type	COMBI G3
Part No.	578 323
Display	Colour touchscreen with backlight
Resistance measuring range	0.001 to 99.9 Ω
Test current	0.2 and 10 A (with EQUITEST 10 A accessory)
Test function	2, 3 and 4-conductor
Interface	Optically isolated on USB, Wi-Fi integrated
Internal test memory	999 measurements
Enclosure material	plastic
Dimensions (l x w x d)	235 x 165 x 75 mm
Weight	1,25 kg
Customs tariff number (Comb. Nomenclature EU)	90318080
GTIN	4013364538634
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.