


## AS TE 20 320 M16 STTZN (621 092)



Figure without obligation



Screwable earth rod connector for creating tested connection options as per DIN EN 62561-1 at the top on the screwable earth rod.

Type	AS TE 20 320 M16 STTZN
Part No.	621 092
Material	HDG steel / StSt
Rod length (l <sub>1</sub> )	320 mm
Earth electrode diameter	20 mm
Thread	M16
Connection	4x M6 x 10 mm  TX30 (4x 2.5 mm <sup>2</sup> – max. 16 mm <sup>2</sup> ) or 1x M8 x 20 mm  AF13 (Ø6–10 mm)
Lightning current carrying capability (10/350 µs) (I <sub>imp</sub> )	100 kA
Short-circuit current (AC 50 Hz / DC) (0.2 s; ≤ 300°C)	5.3 kA (35 mm <sup>2</sup> , stranded)
Max. continuous current load T <sub>max</sub> =100 °C (VDE 0101-2)	125 A
Standard	DIN EN 62561-1
Weight	778 g
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364501140
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.