

HVI LI 20 L6M SR1990 FSP500 GFK AL V2A (819 255)



Figure without obligation



| Type | HVI LI 20 L6M SR1990 FSP500 GFK AL V2A |
|---|---|
| Part No. | 819 255 |
| Material of supporting tube | GRP / Al |
| Length of supporting tube | 1990 mm |
| Transport length | 1990 mm |
| Material of air-termination tip | StSt |
| Length of air-termination tip | 500 mm |
| Diameter Ø conductor | 20 mm |
| Colour of conductor | grey • |
| Material of conductor | Cu |
| RAL colour | similar to 7000 |
| Cross section of core | 19 mm ² |
| Lightning current carrying capability (class / I _{imp}) | H1 / 150 kA |
| Equivalent separation distance s (air) | ≤ 45 cm |
| Material of insulation | PE |
| Material of sheath | PVC |
| Characteristics of sheath | UV stabilized and weather resistant |
| Connection diameter | 10 mm |
| EB connection cable | strip StSt 1000 x 18 x 0.4 mm |
| Material of connection elements | StSt |
| Minimum order length | 6 m |
| Max. gust wind speed | (Max. free length 1,890 mm, 1x HVI light inside) 240 km/h |
| Max. free length | 1890 mm |
| Min. clamping length | 600 mm |
| Standard | DIN IEC/TS 62561-8 (VDE V 0185-561-8) |
| Weight | 5,68 kg |
| Customs tariff number (Comb. Nomenclature EU) | 85389099 |
| GTIN | 4013364255371 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.