

## HVI LI 20 L6M SR2640 FSP1000 GFK AL V2A (819 258)



Figure without obligation



| Type  | HVI LI 20 L6M SR2640 FSP1000 GFK AL V2A                   |
|---|---|
| Part No.  | 819 258   |
| Material of supporting tube                                       | GRP / Al  |
| Length of supporting tube   | 2640 mm   |
| Transport length  | 2640 mm   |
| Material of air-termination tip                                   | StSt  |
| Length of air-termination tip                                     | 1000 mm   |
| Diameter Ø conductor  | 20 mm   |
| Colour of conductor   | grey •  |
| Material of conductor   | Cu  |
| RAL colour  | similar to 7000   |
| Cross section of core   | 19 mm <sup>2</sup>  |
| Lightning current carrying capability (class / I <sub>imp</sub> ) | H1 / 150 kA   |
| Equivalent separation distance s (air)                            | ≤ 45 cm   |
| Material of insulation  | PE  |
| Material of sheath  | PVC   |
| Characteristics of sheath   | UV stabilized and weather resistant                       |
| Connection diameter   | 10 mm   |
| EB connection cable   | strip StSt 2200 x 18 x 0.4 mm                             |
| Material of connection elements                                   | StSt  |
| Minimum order length  | 6 m   |
| Max. gust wind speed  | (Max. free length 3,040 mm, 1x HVI light inside) 201 km/h |
| Max. free length  | 3040 mm   |
| Min. clamping length  | 600 mm  |
| Standard  | DIN IEC/TS 62561-8 (VDE V 0185-561-8)                     |
| Weight  | 6,97 kg   |
| Customs tariff number (Comb. Nomenclature EU)                     | 85389099  |
| GTIN  | 4013364255418   |
| PU  | 1 pc(s)   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.