


Overzicht momentgereedschap

Gereedschappen	Precisie	Instelling	Bijzonderheden	Nm-bereik	Momentbereik					Wisselschachten
					0,01 Nm	0,1 Nm	1 Nm	10 Nm	20 Nm	
iTorque 	± 6 %	variabel	Digitaal display ClickControl Kalibratie-alarm Numerieke schaal-verdeling	0,4 – 1,5 0,8 – 3,0 1,0 – 5,0						Serie 2859   
TorqueVario®-S 	± 10 % ± 6 %/± 10 % ± 6 %	variabel	Numerieke schaal-verdeling	0,04 – 0,46 0,1 – 0,6 0,4 – 1,0 0,5 – 2,0 0,8 – 5,0 2,0 – 7,0						
TorqueVario®-S ESD 	± 10 % ± 6 %/± 10 % ± 6 %			0,04 – 0,46 0,1 – 0,6 0,4 – 1,0 0,5 – 2,0 0,8 – 5,0						
TorqueFix® 	± 6 %	vast	Af fabriek vast ingesteld	16 Versies 0,4 – 7,2						
easyTorque 	± 10 %	vast	Af fabriek vast ingesteld	13 Versies 0,5 – 5,0						Serie 28369 
TorqueFix® Key 	± 6 %	vast	Af fabriek vast ingesteld	0,5 – 4,0						
easyTorque-adapter 	± 10 %	vast	VDE-certificering Af fabriek vast ingesteld	5 Versies 0,8 – 4,0						
TorqueVario®-S VDE 	± 6 %	variabel	VDE-certificering Numerieke schaal-verdeling	0,5 – 2,0 0,8 – 5,0 2,0 – 7,0						
TorqueVario®-S T electric 		variabel	VDE-certificering Numerieke schaal-verdeling	5 – 14						Serie 28379  
Momentsleutel electric 	± 4 %	variabel	VDE-certificering Numerieke schaal-verdeling	5-25						Serie 7207 (3/8") Serie 7209 (1/4")  
TorqueVario®-S T 	± 6 %	variabel	Numerieke schaal-verdeling	5,0 – 14						Serie 2899 
TorqueFix®-T 	± 6 %	vast	Af fabriek vast ingesteld	6 Versies 6,0 – 14						