

ASB 18 Q Select

2-speed cordless combi drill

With brushless motor and QuickIN interface. Perfectly suited to drilling up to 13 mm in metal, stone and masonry.

Part number: 7 113 23 64 00 0



FEIN benefits

- > Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- > QuickIN accessory interface for all QuickIN accessories. Quick change between applications.
- > MultiVolt interface. Cordless tool can be operated with all FEIN Li-ion batteries (12-18 V).
- > 2-speed solid metal gearbox with switchable striking mechanism for drilling in metal, stone and masonry.
- > QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- > Mechanical torque setting.
- > Compact design.
- > 900 screw connections (5x40 mm in wood) with one battery charge (3 Ah).
- > One charger for all FEIN Li-ion batteries of all voltage classes.
- > The battery charge can be read off the battery.
- > FEIN SafetyCell technology. Protects the battery and tool from overload, overheating and total discharge.
- > Extensive user protection features include restart protection, electronic overload protection and brake.

Supplied

- ✓ 1 QuickIN drill chuck (120 Nm)
- ✓ 1 belt clip
- ✓ 1 plastic carrying case
- ✓ 1 magnetic bit storage

Features

- ✓ Removable drill chuck

Technical data

GENERAL TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / HighPower Li-ion
Battery interface	MultiVolt
Motor	brushless
Gearbox	2-speed
Accessory interface	QuickIN
Speed, no load	450 / 2,000 rpm
Impacts	7,360 / 32,000 rpm
Max. torque (hard/soft)	60 / 32 Nm
Torque levels	22 + 1
Drill chuck clamping width	1.5 - 13 mm
Fastening	8 x 300 mm
Capacity in steel Ø	13 mm
Capacity in wood Ø	50 mm
Capacity in stone Ø	13 mm
Tapping	M 10
Weight without storage battery	1.30 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	91 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	102 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	107 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 ahv 3-way	ah,D 1,5 m/s ²
Vibration value 2 ahv 3-way	ah 0,5 m/s ²
Uncertainty of measured value Ka	1,5 m/s ²

Examples of use

