



## ASCD 18-300 W2 AS Impact-tapping-top Set

User set contains a cordless impact wrench/driver

Cordless impact wrench/driver with 1/2" square head tool mounting. The set includes 1/2" VARIO adapter, 5-part FEIN VARIO taper set for through holes and circlip along with a battery (GBA 18 V 5.0 Ah AS) and rapid charger (GAL 1880 CV AS).

Part number: 7 115 10 64 00 0

### FEIN benefits

- > For extreme precision work: The ASCD 18-300 W2 AS with electronic torque setting (6 levels) prevents screw heads from shearing off.
- > Impact wrench/driver-compatible VARIO adapter turns the impact wrench/driver into a tapper, thereby adding a whole new tool to the range of applications.
- > The 5-part FEIN VARIO taper set covers sizes M8, M10, M12, M14, M16.
- > VARIO taper for through holes. Long service life, thanks to high material strength (64 HRC), special cutting geometries suited to impact wrench/drivers and a TiAlN (titanium-aluminium-nitride) coating. The bits experience low levels of wear and friction as well as being heat-resistant to 800 °C. Thanks to the high speeds and number of blows, they can therefore be used in steel up to 900 N/mm<sup>2</sup>.
- > Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- > 1/2" square for holding sockets.
- > Metric screws up to M18 (8.8).
- > Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- > Maximum work progress with AMPShare 18V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge.
- > Ideally equipped for every form of use. Mobile working with the L-BOXX system.

### Supplied

- ✓ 1 x ASCD 18-300 W2 AS (including belt clip, bit holder)
- ✓ 1 X 1/2" VARIO adapter
- ✓ 1 tool case (L-Boxx 136)
- ✓ 1 BATTERY PACK GBA 18 V 5.0 AH AS
- ✓ 1 x 5-part VARIO taper set (M8, M10, M12, M14, M16)
- ✓ 1 rapid charger GAL 1880 CV AS
- ✓ 1 x locking spring

## Technical data

### GENERAL TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Motor	brushless
Speed, no load	0 - 1700 rpm
Impacts	0 - 3400 rpm
Max. torque	290 Nm
Torque levels	6
Tool Holder	1/2" Outer square
Wood screw Ø	8 x 300 mm
Max. metric screw	M18 (8.8)
Weight without storage battery	1.20 kg

### VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	99,2 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	107,2 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	121,5 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 dhv 3-way	ah 15,0 m/s <sup>2</sup>
Uncertainty of measured value Ka	1,5 m/s <sup>2</sup>

## Examples of use



Powered by  **BOSCH**

**Kompatibel mit  
AMPShare- / Bosch  
Professional 18 V  
Akkus.** | Compatible  
with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec  
les batteries 18 V AMPShare/Bosch Professional. |  
Compatible con baterías AMPShare/Bosch  
Professional de 18 V. | Compatibile con le batterie  
AMPShare / Bosch Professional da 18 V.

