

CCG 18-125-15 AS

Cordless angle grinder, 125 mm in diameter



Powerful cordless angle grinder with the same output as a corresponding corded 1500 W device, for effective dividing, grinding and deburring tasks.

Part number: 7 122 09 61 00 0

FEIN benefits

- > Powerful cordless angle grinder with brushless motor, which can handle very tough requirements and industrial applications, especially in combination with the ProCORE 18 V battery technology.
- > Extensive user protection features include soft start, restart protection, kickback monitoring, electronic overload protection, fall monitoring and brake.
- > It's got the knack: manual speed settings via the intuitive control panel allow the speeds to be adapted perfectly to a large range of materials and grinding materials.
- > Secure hold for all applications thanks to non-slip handle.
- > Safety hood, which can be adjusted without the use of tools, and quick-clamping nuts make for short setup times.
- > Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- > COOLPACK 2.0 technology delivers a 135% longer battery life and therefore makes longer operating times possible.
- > State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.
- > ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- > Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Supplied

- ✓ 1 Tool-free quick-clamping nut
- ✓ 1 anti-vibration handle
- ✓ 1 Inner flange
- ✓ 1 safety hood for cutter
- ✓ 1 wheel guard
- ✓ 1 plastic tool case (L-BOXX 238)

Features

- ✓ Brake
- ✓ Restart protection
- ✓ POWERtronic tacho electronics
- ✓ Electronic overload protection
- ✓ Soft start
- ✓ Electronic speed preselection

Application

Roughing-down





Deburring



Dividing



Brushing



★ suitability

★★ optimal suitability

Technical data

GENERAL TECHNICAL DATA

| | |
|--------------------------------|-------------------------|
| Battery voltage | 18 V |
| Battery compatibility | Li-ion / ProCORE Li-ion |
| Battery interface | 18 V AMPShare |
| Motor | brushless |
| Speed, no load | 3,400 - 9,800 rpm |
| Grinding disc Ø | 125 mm |
| Elast. Backing pad Ø | 125 mm |
| Flange | M 14 |
| Weight without storage battery | 2.30 kg |

VIBRATION AND NOISE EMISSION VALUES

| | |
|-----------------------------------|----------------------|
| Sound pressure level LpA | 92 dB |
| Uncertainty of measured value KpA | 3 dB |
| Sound power level LWA | 81 dB |
| Uncertainty of measured value KWA | 3 dB |
| Vibration value 1 dhv 3-way | 6,5 m/s ² |
| Vibration value 2 dhv 3-way | 1,5 m/s ² |
| Uncertainty of measured value Ka | 1,5 m/s ² |

Examples of use



Powered by  **BOSCH**

Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.

