



CCG 18-115-12 PD-SEC AS

PROTAGO cordless angle grinder, 115 mm in diameter

Powerful cordless angle grinder with unique operating concept for particularly safe working.

Part number: 7 122 19 61 00 0

FEIN benefits

- > Maximum user protection thanks to the combination of a number of safety features.
- > Fewer accidents of the type frequently caused by improper use or negligence.
- > Extensive user protection provided by two-handed operation with AutoStop (dead man's switch) and permanently fitted additional handle, non-removable safety hood as well as kick-back monitoring, soft start, restart protection, electronic overload protection and braking function.
- > Low-maintenance FEIN Power Drive motor and AMPShare battery system delivers the same power as a corded 1,200 watt tool for maximum performance and robustness. Optimum speeds, matched to a huge number of different materials using the infinitely variable, electronic speed preselection.
- > Long-life and robust thanks to the fully enclosed motor housing. This protects the motor from aggressive ceramic and mineral dusts. Innovative cooling ribs ensure optimum heat dissipation, including temperature monitoring.
- > Up to 45% more cuts than with the previous system (CCG 18 SEC + FEIN High-Power batteries) thanks to the perfect combination of a powerful tool and the powerful ProCORE battery system. Cutting is up to 16% faster than with comparable competitor devices.
- > Ideal ergonomics for cutting work thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- > Optimum performance, safe handling, perfect ergonomics and simple operation in all work situations.
- > Safe guidance in all work situations thanks to the additional handle, which can be adjusted into 6 positions.
- > Short setup times thanks to the options of tool-free installation and setting, such as those for setting the safety hood, installing the protective cover for cutting work or changing consumables using quick-clamping nuts.
- > Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- > The tried and tested, highly reliable brushless FEIN PowerDrive motors guarantee a very long service life.
- > Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts. Separate motor electronics with dust guard in handle area.
- > Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers.
- > Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- > COOLPACK 2.0 technology delivers a 135% longer battery life and therefore makes longer operating times possible.

- > State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.
- > ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- > Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Supplied

- ✓ 1 Tool-free quick-clamping nut
- ✓ 1 x protective cover for cutting work
- ✓ 1 key
- ✓ 1 plastic tool case (L-BOXX 238)

Features

- ✓ Brake
- ✓ Restart protection
- ✓ Electronic speed preselection
- ✓ POWERtronic tacho electronics
- ✓ Blockage monitoring
- ✓ AutoStop dead man's switch
- ✓ Soft start
- ✓ Electronic overload protection

Application

Roughing-down	★
Deburring	★
Dividing	★
Brushing	★
Satin-finishing	★★

- ★ suitability
- ★★ optimal suitability

Technical data

GENERAL TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Motor	brushless
Speed, no load	2,500 - 8,500 rpm
Grinding disc Ø	115 mm
Elast. Backing pad Ø	115 mm
Flange	M 14
Weight without storage battery	2.40 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	85,7 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	93,7 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	100,3 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 dhv 3-way	7,7 m/s ²
Vibration value 2 dhv 3-way	1,8 m/s ²
Uncertainty of measured value Ka	1,5 m/s ²

Examples of use



Powered by  **BOSCH**

**Kompatibel mit
AMPSHARE-/ Bosch
Professional 18 V
Akkus.** | Compatible
with AMPSHARE/Bosch

Professional 18 V batteries. | Compatible avec
les batteries 18 V AMPSHARE/Bosch Professional. |
Compatible con baterías AMPSHARE/Bosch
Professional de 18 V. | Compatibile con le batterie
AMPSHARE / Bosch Professional da 18 V.



