



## CCG 18-125-12 PD-SEC Set 8Ah ProCORE AS

PROTAGO cordless angle grinder, 125 mm in diameter

Powerful cordless angle grinder with unique operating concept for particularly safe working.

Part number: 7 122 20 62 00 0

### FEIN benefits

- > Maximum user protection thanks to the combination of a number of safety features.
- > Fewer accidents of the type frequently caused by improper use or negligence.
- > Extensive user protection provided by two-handed operation with AutoStop (dead man's switch) and permanently fitted additional handle, non-removable safety hood as well as kick-back monitoring, soft start, restart protection, electronic overload protection and braking function.
- > Low-maintenance FEIN Power Drive motor and AMPShare battery system delivers the same power as a corded 1,200 watt tool for maximum performance and robustness. Optimum speeds, matched to a huge number of different materials using the infinitely variable, electronic speed preselection.
- > Long-life and robust thanks to the fully enclosed motor housing. This protects the motor from aggressive ceramic and mineral dusts. Innovative cooling ribs ensure optimum heat dissipation, including temperature monitoring.
- > Up to 45% more cuts than with the previous system (CCG 18 SEC + FEIN High-Power batteries) thanks to the perfect combination of a powerful tool and the powerful ProCORE battery system. Cutting is up to 16% faster than with comparable competitor devices.
- > Ideal ergonomics for cutting work thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- > Optimum performance, safe handling, perfect ergonomics and simple operation in all work situations.
- > Safe guidance in all work situations thanks to the additional handle, which can be adjusted into 6 positions.
- > Short setup times thanks to the options of tool-free installation and setting, such as those for setting the safety hood, installing the protective cover for cutting work or changing consumables using quick-clamping nuts.
- > Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- > The tried and tested, highly reliable brushless FEIN PowerDrive motors guarantee a very long service life.
- > Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts. Separate motor electronics with dust guard in handle area.
- > Maintenance-free motor with innovative cooling ribs for optimum heat dissipation, including monitoring of temperature.
- > Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers.
- > Delivers the same power as an equivalent corded 1080 W angle grinder.

- > Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- > COOLPACK 2.0 technology delivers a 135% longer battery life and therefore makes longer operating times possible.
- > State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.
- > ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- > Ideally equipped for every form of use. Mobile working with the L-BOXX system.

## Supplied

- ✓ 1 Tool-free quick-clamping nut
- ✓ 1 key
- ✓ 1 x protective cover for cutting work
- ✓ 2 ProCORE 18 V 8.0 Ah battery pack
- ✓ 1 x GAL18 V-160 AS rapid charger
- ✓ 1 plastic tool case (L-BOXX 238)

## Features

- ✓ Brake
- ✓ Soft start
- ✓ Blockage monitoring
- ✓ Electronic overload protection
- ✓ Electronic speed preselection
- ✓ AutoStop dead man's switch

## Application

- Roughing-down
- Deburring
- Dividing
- Brushing
- Satin-finishing



- ★ suitability
- ★★ optimal suitability

## Technical data

### GENERAL TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Motor	brushless
Speed, no load	2,500 - 8,500 rpm
Grinding disc Ø	125 mm
Elast. Backing pad Ø	125 mm
Flange	M 14
Weight with battery	3.30 kg
Weight without storage battery	2.40 kg

### VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	84,9 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	92,9 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	99,3 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 dhv 3-way	8,8 m/s <sup>2</sup>
Vibration value 2 dhv 3-way	2,1 m/s <sup>2</sup>
Uncertainty of measured value Ka	1,5 m/s <sup>2</sup>

## Examples of use



Powered by  **BOSCH**

**Kompatibel mit  
AMPSHARE-/ Bosch  
Professional 18 V  
Akkus.** | Compatible  
with AMPSHARE/Bosch

Professional 18 V batteries. | Compatible avec  
les batteries 18 V AMPSHARE/Bosch Professional. |  
Compatible con baterías AMPSHARE/Bosch  
Professional de 18 V. | Compatibile con le batterie  
AMPSHARE / Bosch Professional da 18 V.

