

MULTIMASTER AMM 700 1.7 Q Joint Renovation

Battery-powered oscillating multi-tool

Our best MultiTool specially for grouting renewal with durable 12-star receptacle and 7 blades for cutting out elastic joints.

Part number: 7 129 37 64 00 0



FEIN benefits

- > Precision – MultiTools get into hard-to-reach places. Thanks to vibration damping, they work quietly and precisely.
- > Versatility – blade lengths up to 98 mm allow even very deep joints to be cut. The diamond-coated cleaning blade cleans mortar flanks before you fill them in again.
- > Safety and simplicity – MultiTools work precisely and safely in the joint. Blades don't break and the power tool is protected against overload and overheating. Misuse is almost impossible.
- > Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- > QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- > 12-sided holder for optimum torque transfer.
- > 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering great efficiency, ability to handle extreme loads and a long service life.
- > Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- > Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- > Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- > The COOLPACK technology ensures a longer battery life and therefore makes long operating periods possible.
- > The battery charge can be read off the battery.
- > Compatible with AMPShare/Bosch Professional 18 V batteries.
- > Ideally equipped for every job. Mobile working with the L-BOXX system.

Supplied

- ✓ 5 Cutter blades, straight (form 117) 6 390 31 17 01 5
- ✓ 1 handle
- ✓ 1 plastic tool case (L-BOXX 238)
- ✓ 1 Cutter blade, straight, long (form 116) 6 390 31 16 01 1
- ✓ 1 protective cover for tool changes
- ✓ 1 Cutter blade, mushroom shaped 6 390 31 28 01 2
- ✓ 1 sharpening stone (63719010014)

Technical data

GENERAL TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Oscillations	10,000 - 19,500 rpm
Tool Holder	12-sided
Tool change	QuickIN
Amplitude	2 x 1,7°
Weight without storage battery	1.10 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	77,0 dB
Uncertainty of measured value KpA	3,0 dB
Sound power level LWA	85,0 dB
Uncertainty of measured value KWA	3,0 dB
Sound peak value LpCpeak	90,3 dB
Uncertainty of measured value KpCpeak	3,0 dB
Uncertainty of measured value Ka	1,5 m/s ²

Examples of use

