

## ABLK 18 1.3 CSE AS Set 1x 5 Ah

Cordless nibbler up to 1.3 mm



Compact and curve-compatible nibbler for roof and façade construction. Precise cuts in trapezoid and corrugated sheet metals and profiles. Includes battery charger GAL 1880 CV AS, 1x Li-ion storage batteries GBA 18V 5.0 Ah AS, additional punch and die set, permanent marker, painter's tape and metre rule.

Part number: 7 132 10 63 00 0

### FEIN benefits

- > 66 m cutting capacity (in 0.8 mm sheet metal) with one battery charge (5 Ah).
- > Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- > Optimum handling due to extremely slim gearbox head.
- > 1.9 m/min cutting speed for excellent work progress.
- > Variable cutting speed due to electronically adjustable speed control.
- > Brief overlapping area up to 2.6 mm.
- > Rotating punch for a service life which is now up to 30 % longer.
- > Proven MultiMaster motor with outstanding performance and stability.
- > QuickIN quick change system for die and punch.
- > Low operating costs. Punch and die are replaced independently of one another.
- > Compatible with AMPShare/Bosch Professional 18 V batteries.
- > Maximum work progress with AMPShare 18V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge.
- > Ideally equipped for every job. Mobile working with the L-BOXX system.
- > State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.

### Supplied

- |   |  |                                     |
|---|--|-------------------------------------|
| ✓ 1 die for corrugated sheet metal (30109169009) fitted     | ✓ 1 punch (6 36 02 050 00 0)                   | ✓ 1 punch and die set (30109169030) |
| ✓ 1 permanent marker (32133037000)                          | ✓ 1 painter's tape (32133038000)               | ✓ 1 metre rule (18750283000)        |
| ✓ 1 Li-ion storage battery GBA 18 V 5.0 Ah AS (92604346020) | ✓ 1 rapid charger GAL 1880 CV AS (92604335010) | ✓ 1 tool case (L-Boxx 136)          |

### Features

- |                        |           |                     |
|------------------------|-----------|---------------------|
| ✓ Rotating round punch | ✓ QuickIN | ✓ Adjustable stroke |
|------------------------|-----------|---------------------|

## Application

Notches	★★
Coil sections	★
Interior cut-outs	★★
Profile sections	★★
Curve cuts	★★

★ suitability

★★ optimal suitability

## Technical data

### GENERAL TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Strokes	1 000 - 1 600 rpm
Cutting speed	1.9 m/min
Steel up to 400 N/mm <sup>2</sup>	1.3 mm
Steel up to 600 N/mm <sup>2</sup>	0.8 mm
Steel up to 800 N/mm <sup>2</sup>	0.6 mm
Non-ferrous metals up to 250 N/mm <sup>2</sup>	2 mm
Cutting width	4 mm
Immersion Ø with die	19 mm
Rad. of smallest curve (inside/outside)	15 / 20 mm
Weight without storage battery	1.68 kg

### VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	79,9 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	87,9 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	111,6 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 dhv 3-way	ah 3,8 m/s <sup>2</sup>
Uncertainty of measured value Ka	1,5 m/s <sup>2</sup>

## Examples of use

