



## ABH 18-26 AS Set 5 Ah

Cordless rotary hammer drill

With SDS plus and an impact energy of 2.6 joules for drilling up to 26 mm in concrete.

Part number: 7 140 03 62 00 0

### FEIN benefits

- > The powerful, brushless motor delivers 2.6 joules of impact energy and ensures rapid drilling progress as well as high chisel grinding capacity.
- > Kickback monitoring with intelligent rapid shutdown should the hammer drill kick back suddenly for optimum user protection.
- > Electronic Precision Control (EPC) slowly ramps up the working speed for perfect handling and control when working with sensitive materials and challenging surfaces.
- > Simple and precise speed control using the throttle.
- > Fatigue-free working thanks to compact design and few vibrations.
- > Change the chisel position (Vario-Lock) – lock the chisel in 36 positions for the optimum working position every time.
- > Bright working area thanks to integrated LED light.
- > Clamps or hooks the bit if the drive to the drill spindle is interrupted.
- > Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- > Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- > ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- > Ideally equipped for every form of use. Mobile working with the L-BOXX system.

### Supplied

- ✓ 1 handle
- ✓ 1 tool case (L-Boxx 136)
- ✓ 1 depth stop
- ✓ 2 Li-Ion storage battery GBA 18V 5.0 Ah AS
- ✓ 1 x tool cloth
- ✓ 1 rapid charger GAL 1880 CV AS

## Technical data

### GENERAL TECHNICAL DATA

Battery voltage	18 V
Battery capacity	5 Ah
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Motor	brushless
Speed, no load	0 - 980 rpm
Impacts	0 - 4,350 rpm
Impact energy	2.6 J
Tool Holder	SDS-plus
Hole diameter, concrete	26 mm
Hole diameter, masonry	68 mm
Capacity in steel Ø	13 mm
Capacity in wood Ø	30 mm
Weight without storage battery	3.20 kg

### VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	88 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	99 dB
Uncertainty of measured value KWA	3 dB
Vibration value 1 ahv 3-way	ah,D 15,2 m/s <sup>2</sup>
Vibration value 2 ahv 3-way	ah,D 9,9 m/s <sup>2</sup>
Uncertainty of measured value Ka	1,5 m/s <sup>2</sup>

## Examples of use



Powered by  **BOSCH**

**Kompatibel mit  
AMPShare-/ Bosch  
Professional 18 V  
Akkus.** | Compatible  
with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec  
les batteries 18 V AMPShare/Bosch Professional. |  
Compatible con baterías AMPShare/Bosch  
Professional de 18 V. | Compatibile con le batterie  
AMPShare / Bosch Professional da 18 V.

