

WBP 10

Angle drill up to 10 mm

Extremely small angle drill for working in difficult-to-reach spots.

Part number: 7 205 51 60 00 0



FEIN benefits

- > FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- > Particularly flat and slim design with 17 mm width across corners and 96 mm gearbox head height for work in tight spaces and corners.
- > Flexible and universal use thanks to clockwise and reverse running for thread cuts up to M6.
- > Metal gear head.
- > Tapered drill shaft.
- > High-precision metal drill chuck.
- > High concentricity.
- > Distortion-free barrel-type motor housing.
- > FEIN Sensitive Handle.
- > 5 metre cable.

Supplied

- ✓ 1 3-jaw chuck up to Ø 10 mm
- ✓ 1 drill chuck key

Technical data

GENERAL TECHNICAL DATA

Input	500 W
Output	270 W
Speed, full load	0 - 1,030 rpm
Speed, no load	0 - 1,830 rpm
Torque at max. output power	8 Nm
Stall torque	21 Nm
Drill chuck clamping width	0.8 - 10 mm
Capacity in steel Ø	10 mm
capacity in Ø stainless steel	10 mm
Capacity in alu Ø	15 mm
Capacity in wood Ø	25 mm
Tapping	M 6
Cone at drill shaft	B 10
Width across corners	17 mm
Gearbox head height	96
Cable with plug	5 m
Weight according to EPTA	1.50 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	86,3 dB
Uncertainty of measured value KpA	5 dB
Sound power level LWA	94,3 dB
Uncertainty of measured value KWA	5 dB
Sound peak value LpCpeak	101 dB
Uncertainty of measured value KpCpeak	5 dB
Vibration value 1 dhv 3-way	3 m/s ²
Uncertainty of measured value Ka	1,5 m/s ²

Examples of use

