

BOP 10

Hand Drill up to 10 mm

Compact single-speed drill with speed stability, up to 10 mm in steel for on-site installation work.

Part number: 7 205 53 60 00 0



FEIN benefits

- > Particularly flat and slim design with excellent width across corners for installation work even in tight spaces and corners.
- > FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- > Metal gear head and distortion-free barrel-type motor housing for superb service life.
- > Reversible.
- > High-precision metal drill chuck.
- > High concentricity.
- > Self-tightening drill chuck clamping jaws.
- > FEIN Sensitive Handle.
- > Variable speed control.
- > 5 metre cable.
- > 43 mm diameter collar for use in the drill jig.

Supplied

- ✓ 1 SUPRA SKE single sheath metal quick clamping drill chuck
- ✓ 1 additional handle

Features

- ✓ Reversible rotation
- ✓ Acceleration electronics

Application

Twist drilling



Tapping



Countersinking



★ suitability

★★ optimal suitability

Technical data

GENERAL TECHNICAL DATA

Input	500 W
Output	270 W
Speed, full load	0 - 900 rpm
Speed, no load	0 - 1,500 rpm
Torque at max. output power	9 Nm
Stall torque	24 Nm
Drill chuck clamping width	1.5 - 13 mm
Capacity in steel Ø	10 mm
capacity in Ø stainless steel	10 mm
Capacity in alu Ø	15 mm
Capacity in wood Ø	30 mm
Tapping	M 6
Thread of spindle	1/2"-20 UNF
Collar Ø	43 mm
Width across corners	23 mm
Cable with plug	5 m
Weight according to EPTA	1.80 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	85,6 dB
Uncertainty of measured value KpA	5 dB
Sound power level LWA	93,6 dB
Uncertainty of measured value KWA	5 dB
Sound peak value LpCpeak	99,8 dB
Uncertainty of measured value KpCpeak	5 dB
Vibration value 1 dhv 3-way	ah,D 3,0 m/s ²
Uncertainty of measured value Ka	1,5 m/s ²

Examples of use

