

## BOP 10-2

### Two-Speed Hand Drill up to 10 mm

Universal two-speed drill, up to 10 mm with ideal speed range for steel and stainless steel.

Part number: 7 205 54 60 00 0



### FEIN benefits

- > Mechanical two-speed gearbox for optimum speed adjustment for a wide range of uses.
- > FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- > Metal gear head and distortion-free barrel-type motor housing for superb service life.
- > Reversible.
- > High-precision metal drill chuck.
- > High concentricity.
- > Self-tightening drill chuck clamping jaws.
- > FEIN Sensitive Handle.
- > Variable speed control.
- > 5 metre cable.
- > 43 mm diameter collar for use in the drill jig.

### Supplied

- ✓ 1 SUPRA SKE single sheath metal quick clamping drill chuck
- ✓ 1 additional handle

### Features

- ✓ Reversible rotation
- ✓ Acceleration electronics

### Application

Twist drilling



Tapping



Countersinking



★ suitability

★★ optimal suitability

## Technical data

### GENERAL TECHNICAL DATA

Input	500 W
Output	270 W
Speed, full load	0 - 460 / 0 - 1,350 rpm
Speed, no load	0 - 700 / 0 - 2,250 rpm
Torque at max. output power	20 / 7 Nm
Stall torque	50 / 16 Nm
Drill chuck clamping width	1.5 - 13 mm
Capacity in steel Ø	10 mm
capacity in Ø stainless steel	10 mm
Capacity in alu Ø	16 mm
Capacity in wood Ø	35 mm
Tapping	M 10
Thread of spindle	1/2"-20 UNF
Collar Ø	43 mm
Width across corners	23 mm
Cable with plug	5 m
Weight according to EPTA	2.00 kg

### VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	84,8 dB
Uncertainty of measured value KpA	5 dB
Sound power level LWA	92,8 dB
Uncertainty of measured value KWA	5 dB
Sound peak value LpCpeak	99,1 dB
Uncertainty of measured value KpCpeak	5 dB
Vibration value 1 dhv 3-way	ah,D 3,0 m/s <sup>2</sup>
Uncertainty of measured value Ka	1,5 m/s <sup>2</sup>

## Examples of use

