

BOP 13-2 set

Two-Speed Hand Drill up to 13 mm

Universal two-speed drill, up to 13 mm with ideal speed range for steel and stainless steel.

Part number: 7 205 55 61 00 0



FEIN benefits

- > Mechanical two-speed gearbox for optimum speed adjustment for a wide range of uses.
- > FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- > Metal gear head and distortion-free barrel-type motor housing for superb service life.
- > Reversible.
- > High-precision metal drill chuck.
- > High concentricity.
- > Self-tightening drill chuck clamping jaws.
- > FEIN Sensitive Handle.
- > Variable speed control.
- > 5 metre cable.
- > 43 mm diameter collar for use in the drill jig.

Supplied

- ✓ 1 SUPRA SKE single sheath metal quick clamping drill chuck
- ✓ 1 additional handle
- ✓ 1 plastic carrying case

Features

- ✓ Reversible rotation
- ✓ Acceleration electronics

Application

Twist drilling



Tapping



Countersinking



★ suitability

★★ optimal suitability

Technical data

GENERAL TECHNICAL DATA

| | |
|-------------------------------|-------------------------|
| Input | 550 W |
| Output | 300 W |
| Speed, full load | 0 - 440 / 0 - 1,300 rpm |
| Speed, no load | 0 - 680 / 0 - 2,200 rpm |
| Torque at max. output power | 20 / 7 Nm |
| Stall torque | 50 / 16 Nm |
| Drill chuck clamping width | 1.5 - 13 mm |
| Capacity in steel Ø | 13 mm |
| capacity in Ø stainless steel | 13 mm |
| Capacity in alu Ø | 16 mm |
| Capacity in wood Ø | 37 mm |
| Tapping | M 10 |
| Thread of spindle | 1/2"-20 UNF |
| Collar Ø | 43 mm |
| Width across corners | 23 mm |
| Cable with plug | 5 m |
| Weight according to EPTA | 2.00 kg |

VIBRATION AND NOISE EMISSION VALUES

| | |
|---------------------------------------|---------------------------|
| Sound pressure level LpA | 85 dB |
| Uncertainty of measured value KpA | 5 dB |
| Sound power level LWA | 93 dB |
| Uncertainty of measured value KWA | 5 dB |
| Sound peak value LpCpeak | 99,2 dB |
| Uncertainty of measured value KpCpeak | 5 dB |
| Vibration value 1 dhv 3-way | ah,D 3,0 m/s ² |
| Uncertainty of measured value Ka | 1,5 m/s ² |

Examples of use

