

GWP 10

Thread drill up to M 10

Fast, accurate thread drill with reversing gear for shorter working times.

Part number: 7 209 38 60 00 0



FEIN benefits

- > Unique speed thanks to reversing gear for automatic reversal of rotation direction when retracting drill spindle from threaded hole. Rapid return action at 680 rpm for shorter cycle times.
- > Outstanding precision due to clearance-free connection of drill shaft and threaded chuck with B12 taper mounting for high concentricity. Positive fit of thread drill in chuck for the best results.
- > FEIN sensitive handle for applying feed force in the direct drilling axis while ensuring an ideal position in the guiding hand.
- > FEIN high-power motor with stable speed.
- > Small width across corners of 23 mm.
- > Metal gear head.
- > Distortion-free barrel-type motor housing.

Supplied

- ✓ 1 additional handle
- ✓ Threaded chuck not included

Technical data

GENERAL TECHNICAL DATA

Input	450 W
Output	250 W
Idling speed in reverse running	0 - 1,000 rpm
Load speed when cutting	0 - 450 rpm
Load speed in reverse running	0 - 680 rpm
Torque at max. output power	21 Nm
Stall torque	53 Nm
Thread in steel up to	M 10
Thread in stainless steel	M 10
Cone at drill shaft	B 12
Collar Ø	43 mm
Width across corners	23 mm
Cable with plug	5 m
Weight according to EPTA	1.60 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	86,1 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	94,1 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	100,1 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 dhv 3-way	3,0 m/s ²
Uncertainty of measured value Ka	1,5 m/s ²

Examples of use

