



## WPO 14-15 E Set

### Polishers

Extremely powerful angle polisher for vehicle and boat repairs.

Part number: 7 221 48 51 01 0

### FEIN benefits

- > Ideal speed range with infinitely variable speed control for professional surface processing on vehicles and boats.
- > Maximum speed stability at any load over the full setting range thanks to mechanical gear reduction in conjunction with the FEIN high-power motor.
- > Special system accessories for the efficient refurbishment of used car paintwork, new car paintwork and highly scratch-resistant paints, and for cleaning, sanding and polishing boat surfaces and gelcoat layers.
- > Convenient speed adjustment.
- > Does not heat up in continuous use.
- > Handle cover for excellent ergonomics.
- > Spindle lock.
- > Right or left-handed operation.
- > Restart protection.
- > Soft start.
- > Carbon brushes with self cut-off function.
- > Can be converted to rotary sander with extractor hood and backing pad.
- > Tool also available without accessories (7 221 48).

### Supplied

- ✓ 1 anti-vibration handle
- ✓ 1 Grip hood
- ✓ 1 Support plate with Velcro attachment, Ø 150 mm
- ✓ 1 Polishing sponge, Ø 150 mm, medium

### Features

- ✓ Soft start
- ✓ Restart protection
- ✓ FEIN high-power motor
- ✓ Spindle lock

### Application

Polishing





Rough sanding



Fine sanding



Dry sanding



Micro-sanding



★ suitability

★★ optimal suitability

## Technical data

### GENERAL TECHNICAL DATA

Input	1,200 W
Output	750 W
Speed, no load	500 - 1,500 rpm
Polishing disc Ø	230 mm
Mounting thread	M 14
Cable with plug	4 m
Weight according to EPTA	2.50 kg

### VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	84 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	95 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	100 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 ahv 3-way	ah,P 2,5 m/s <sup>2</sup>
Vibration value 2 ahv 3-way	ah,SG 2,5 m/s <sup>2</sup>
Uncertainty of measured value Ka	1,5 m/s <sup>2</sup>

## Examples of use

