

WPO 14-25 E - Stainless steel start set

Stainless steel start set

Stainless steel starter set for standard applications in surface machining.

Part number: 7 221 49 50 01 0



FEIN benefits

- > Extremely powerful even at low speeds thanks to mechanical gear reduction and FEIN high power motor.
- > Infinitely variable speed, ideal for sanding, satin finishing, brushing and high-gloss polishing of stainless steel.
- > Universal suitability as fully-functional sander, polisher and satin-finisher.
- > Excellent handling.
- > Spindle lock.
- > Right or left-handed operation.
- > Restart protection.
- > Soft start.
- > H 07 industrial cable.
- > Dustproof ball bearing.
- > Carbon brushes with self cut-off function.
- > Wide range of accessories.

Supplied

- ✓ 1 holder, rotating
- ✓ 1 corrugated sanding fleece
- ✓ 1 elastic sanding roller (100 x 100 mm, grain 60)
- ✓ 1 anti-vibration handle
- ✓ safety guard
- ✓ 1 supporting plate with velcro adhesion section (Ø 115 mm, M14)
- ✓ 1 lamella fleece cylinder (100 x 100 mm, grain 180)
- ✓ 1 plastic carrying case
- ✓ 1 work arbour
- ✓ 10 sanding fleeces with velcro (Ø 115 mm, fine)
- ✓ 2 keys

Features

- ✓ Soft start
- ✓ Spindle lock
- ✓ Restart protection
- ✓ FEIN high-power motor

Application

Polishing



Rough sanding





Fine sanding



Dry sanding



Micro-sanding



★ suitability

★★ optimal suitability

Technical data

GENERAL TECHNICAL DATA

Input	1,200 W
Output	750 W
Sanding pad Ø	230 mm
Speed, no load	900 - 2,500 rpm
Polishing disc Ø	230 mm
Mounting thread	M 14
Cable with plug	4 m
Weight according to EPTA	2.50 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	84 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	95 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	100 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 ahv 3-way	ah,P 3,5 m/s ²
Vibration value 2 ahv 3-way	ah,SG 2,5 m/s ²
Uncertainty of measured value Ka	1,5 m/s ²

Examples of use

