

KS 10-38 E set

Fillet weld grinder

Fillet weld grinder for difficult-to-reach spots in metal constructions.

Part number: 7 221 67 60 00 0



FEIN benefits

- > Flexible use thanks to drive head that can be swivelled without the need for tools.
- > Flat design for corners, angles and difficult-to-reach spots.
- > Long belt drive service life thanks to zero-maintenance tensioning system.
- > Spindle brake for quick tool changes.
- > Spark hood can be adjusted and removed without the need for tools.
- > Electronic speed setting.
- > Made in Germany quality.
- > H 07 industrial cable.
- > Soft start.
- > Restart protection.

Supplied

- ✓ 1 anti-vibration handle
- ✓ Profiling stone for profiling the fleece discs
- ✓ Medium fleece discs, diameter 150 mm, one 3 mm thick and one 6 mm thick
- ✓ 1 plastic carrying case
- ✓ Fine fleece discs, diameter 150 mm, one 3 mm thick and one 6 mm thick

Features

- ✓ Soft start
- ✓ Restart protection
- ✓ FEIN high-power motor

Application

Polishing	★ ★
Rough sanding	★ ★
Fine sanding	★ ★
Dry sanding	★ ★



Micro-sanding



- ★ suitability
- ★★ optimal suitability

Technical data

GENERAL TECHNICAL DATA

Input	800 W
Output	550 W
Speed, no load	1,350 - 3,750 rpm
Peripheral speed	29.5 m/sec
Tool diameter	150 mm
Cable with plug	4 m
Weight according to EPTA	3.20 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	85 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	96 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	101 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 ahv 3-way	ah,P/T=3 2,5 m/s ²
Vibration value 2 ahv 3-way	ah,P/T=6 5,0 m/s ²
Uncertainty of measured value Ka	1,5 m/s ²

Examples of use

