



MULTIMASTER MM 500 Plus Top

Oscillating multi-tool – MM 500

The powerful MultiTool for rapid work progress (in interior work and renovation) with more than 30 accessories for sawing in wood and metal, sanding, removing tiles and much more.

Part number: 7 229 67 70 00 0

FEIN benefits

- > Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- > StarlockPlus tool mounting: more work progress and greater precision thanks to 100% power transmission without losses.
- > QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- > With the StarlockPlus tool mounting, you can access around 100 FEIN accessories from the Starlock and StarlockPlus performance classes.
- > 350 W FEIN motor. Powerful motor with a high copper content, which is suited to overload for a higher cutting speed and faster work progress.
- > Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- > Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- > Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- > Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- > Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Supplied

- ✓ 1 E-Cut long-life saw blade (10 mm)
- ✓ 1 E-Cut carbide Pro saw blade (32 mm)
- ✓ 1 Stopper knife
- ✓ 1 dust extraction device
- ✓ 2 E-Cut long-life saw blades (35 mm)
- ✓ 1 carbide saw blade (diameter 75 mm)
- ✓ 1 Sanding plate with holes
- ✓ 1 tool case (L-BOXX 136)
- ✓ 2 E-Cut long-life saw blades (65 mm)
- ✓ 1 HM rasp (triangular)
- ✓ with 5 sanding sheets, with holes for each of grit sizes 60, 80, 120, 180

Technical data

GENERAL TECHNICAL DATA

Input	350 W
Oscillations	10,000 - 19,500 rpm
Tool Holder	StarlockPlus
Tool change	QuickIN
Amplitude	2 x 1,7°
Cable with plug	5 m
Weight according to EPTA	1.40 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	72 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	83 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	84 dB
Uncertainty of measured value KpCpeak	3 dB

Examples of use

