



MULTIMASTER MM 700 Max

Oscillating multi-tool – MM 700

Our best MultiTool for the most rapid work progress in interior work and renovation with a bimetal saw blade for wood, metal and plastics.

Part number: 7 229 68 63 00 0

FEIN benefits

- › Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- › StarlockMax tool mounting: more work progress and greater precision thanks to 100% power transmission without losses.
- › QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- › With the StarlockMax tool mounting, you can access around 180 FEIN accessories from the Starlock, Starlock Plus and StarlockMax performance classes.
- › 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- › Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- › Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- › Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- › Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- › Electronic safety cut-off – user protection should the saw blade lock, for example.
- › Ideally equipped for every job. Mobile working with the L-BOXX system.

Supplied

- ✓ 1 Universal E-Cut saw blade (44 mm)
- ✓ 1 tool case (L-BOXX 136)

Features

- ✓ Mechanical interface

Technical data

GENERAL TECHNICAL DATA

| | |
|--------------------------|---------------------|
| Input | 450 W |
| Output | 250 W |
| Oscillations | 10,000 - 19,500 rpm |
| Tool Holder | StarlockMax |
| Tool change | QuickIN |
| Amplitude | 2 x 2,0° |
| Cable with plug | 5 m |
| Weight according to EPTA | 1.60 kg |

VIBRATION AND NOISE EMISSION VALUES

| | |
|---------------------------------------|-------|
| Sound pressure level LpA | 85 dB |
| Uncertainty of measured value KpA | 3 dB |
| Sound power level LWA | 96 dB |
| Uncertainty of measured value KWA | 3 dB |
| Sound peak value LpCpeak | 97 dB |
| Uncertainty of measured value KpCpeak | 3 dB |

Examples of use

