

MULTIMASTER MM 700 1.7 Q Bus & Truck

Oscillating multi-tool – MM 700

Our best oscillating MultiMaster including an extensive set of accessories for work on cars and commercial vehicles.

Part number: 7 229 70 64 00 0



FEIN benefits

- > Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- > QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- > Hexagonal tool holder for optimum torque transfer.
- > 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- > Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- > Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- > Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- > Ideally equipped for every job. Mobile working with the L-BOXX system.

Supplied

- ✓ 1 Hook-shaped cutter blade, toothed (form 217)
- ✓ 1 Spade-shaped scraper knife, with scratch-protective coating (form 105)
- ✓ 2 L-shaped cutter blades, toothed (form 207)
- ✓ 2 Straight cutter blades, toothed (form 073)
- ✓ 1 Straight cutter blades, curved shape, Z-bend (form 072)
- ✓ 1 U-shaped cutter blade, toothed (form 212)
- ✓ 2 straight cutter blades, Z-bend, toothed (form 081)
- ✓ 1 L-shaped cutter blade, toothed (form 209)
- ✓ 1 protective cover for tool changes
- ✓ 1 traction cable with fastening
- ✓ 1 sharpening stone (63719010014)
- ✓ 1 tool case (L-BOXX 136)

Technical data

GENERAL TECHNICAL DATA

Input	450 W
Output	250 W
Oscillations	10,000 - 19,500 rpm
Tool Holder	12-sided
Tool change	QuickIN
Amplitude	2 x 1,7°
Cable with plug	5 m
Weight according to EPTA	1.65 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	85,0 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	96,0 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	97,0 dB
Uncertainty of measured value KpCpeak	3 dB

Examples of use

