

BLK 2.0 E Set

Nibbler up to 2 mm



Compact nibbler with unlimited curve compatibility for recesses and cut-outs in material thicknesses of up to 2 mm. Includes additional punch and die set, permanent marker, painter's tape and metre rule.

Part number: 7 232 40 61 00 0

FEIN benefits

- > High curve precision due to special cutting head geometry. Nibbler can turn on the spot.
- > Especially well-suited for cutting edged sheet metals with a minimum bend radius of 3 mm.
- > Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- > QuickIN clamping system.
- > Optimal ergonomics.
- > Motor with outstanding performance and stability.
- > Ideal for cut-outs.
- > Optimally suited for template cuts.
- > Chip protection mesh on vent slots.
- > 5 metre cable.
- > Stainless steel up to 1.0 mm.

Supplied

- ✓ 1 die (3 13 09 040 00 2)
- ✓ 1 punch (6 36 02 051 00 9)
- ✓ 1 punch and die set (63602051018)
- ✓ 1 permanent marker (32133037000)
- ✓ 1 painter's tape (32133038000)
- ✓ 1 metre rule (18750283000)
- ✓ 1 tool case (L-BOXX 136)

Features

- ✓ QuickIN
- ✓ Adjustable stroke

Application

Notches	★ ★
Interior cut-outs	★ ★
Profile sections	★ ★



Curve cuts



- ★ suitability
- ★★ optimal suitability



Technical data

GENERAL TECHNICAL DATA

Input	350 W
Output	210 W
Strokes	500 - 1,000 rpm
Cutting speed	1 m/min
Steel up to 400 N/mm ²	2 mm
Steel up to 600 N/mm ²	1.5 mm
Steel up to 800 N/mm ²	1 mm
Non-ferrous metals up to 250 N/mm ²	2.5 mm
Cutting width	8 mm
Immersion Ø with die	18 mm
Rad. of smallest curve (inside/outside)	4 / 0 mm
Cable with plug	5 m
Weight according to EPTA	1.80 kg

VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	87,9 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	95,9 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	117,9 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 dhv 3-way	7,3 m/s ²
Uncertainty of measured value Kα	1,5 m/s ²

Examples of use

