



## BLK 5.0 E

Nibbler up to 5 mm

Powerful nibbler for heavy dismantling and cutting applications.

Part number: 7 232 47 61 00 0

### FEIN benefits

- > Suited to cuts over 90° edges, for example on guard rails or during tank decommissioning.
- > Incredible power delivered by the 1700 W motor while also offering outstanding ergonomics and optimum power-to-weight ratio.
- > Extensive user protection: restart protection, blocking protection, overload protection, soft start.
- > Cutting direction: 4 x 90°, can be adjusted without the need for tools.
- > Variable stroke.
- > Tool-free quick change system for die and punch.
- > Ergonomic handle suited to guiding in all directions.
- > Chip protection mesh in fan area.
- > Wide range of accessories.

### Supplied

- ✓ 1 die 5, steel (31309107000) fitted
- ✓ 1 punch 5/P5 steel (31309141000) fitted
- ✓ 1 additional handle fitted
- ✓ 1 plastic tool case (L-BOXX 238)

### Features

- ✓ QuickIN
- ✓ Additional handle
- ✓ Adjustable stroke

### Application

Notches	★★
Interior cut-outs	★
Profile sections	★★
Curve cuts	★

- ★ suitability
- ★★ optimal suitability

## Technical data

### GENERAL TECHNICAL DATA

Input	1,700 W
Output	1,000 W
Strokes	260 - 820 rpm
Cutting speed	1,5 m/min
Steel up to 400 N/mm <sup>2</sup>	5 mm
Steel up to 600 N/mm <sup>2</sup>	3.3 mm
Steel up to 800 N/mm <sup>2</sup>	2.5 mm
Non-ferrous metals up to 250 N/mm <sup>2</sup>	7 mm
Cutting width	8 mm
Immersion Ø with die	43 mm
Rad. of smallest curve (inside/outside)	90 / mm
Cable with plug	4 m
Weight according to EPTA	3.80 kg

### VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	93,2 dB
Uncertainty of measured value KpA	3 dB
Sound power level LWA	101,2 dB
Uncertainty of measured value KWA	3 dB
Sound peak value LpCpeak	125 dB
Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 dhv 3-way	12,4 m/s <sup>2</sup>
Uncertainty of measured value Ka	1,5 m/s <sup>2</sup>

## Examples of use

