

MBS 25 F

Magnetic Drill Jigs

Flexible magnetic drill jig with fine adjustment for rotary drills with up to 23 mm drill capacity.

Part number: 9 03 22 223 00 0



FEIN benefits

- > Universal suitability for drilling, tapping, reaming and countersinking.
- > Fine adjustment of the drill spindle for convenient tool alignment.
- > Double drill motor guide for use with very large drilling tools.
- > Feed handwheel can be moved from one side to the other.
- > Integrated coolant tank with flexible jointed hose.
- > High magnetic holding force.
- > Carriage height adjustable without tools.

Supplied

- ✓ 1 coolant tank
- ✓ 1 lashing strap
- ✓ 1 contact guard
- ✓ 1 reducing ring, diameter 43 mm



Technical data

GENERAL TECHNICAL DATA

Input	100 W
Socket max.	16 A
For collar Ø	53 mm
Twist drill max. Ø	25 mm
Tapping	M 20
Countersinking max. Ø	50 mm
Reaming max. Ø	25 mm
Stroke	145 mm
Total stroke range	290 mm
Adjustment range for drill jigs	6 mm
Swivel range for drill jigs	7°
Magnetic holding power	14,000 N
Magnetic foot dimensions	205 x 95 mm
Cable with plug	4 m
Weight according to EPTA	12.50 kg