



## Cordless jigsaw ASTS 18-26 AS (in box)

Cordless jigsaw for metal and timber, 26 mm stroke

Powerful, versatile jigsaw for metal and wood for precise and curved cuts, also overhead.

Part number: 9 910 00 01 56 1

### FEIN benefits

- > Optimum control thanks to narrow and ergonomic baton handle for precise cuts, as well as cornered cuts in very tight spaces.
- > Thanks to speed and pendulum stroke adjustment options, optimal work results are guaranteed on a variety of materials without the need for rework.
- > More options – there are no limits on the flexible machining of a huge range of materials (e.g. steel, aluminium and plastic) thanks to rapid saw blade changes without the need for tools. The automatic saw blade lock makes it easier to change sharp-edged saw blades without having to reach round and reduces the risk of injury.
- > Dust adapter for clean and ergonomic work.
- > 4-step pendulum stroke for optimal adjustment of cutting speed, cutting performance, and cutting pattern to the material being processed.
- > Well lit working area thanks to intelligent LED working lamp, with overhead cut-off function.
- > The fan wheel's exhaust is concentrated onto the saw blade, which enables an unobstructed view of the cut edge.
- > Cold cuts for cuts with virtually no sparks or burrs.
- > Electronic user protection: Overload shutdown to prevent permanent damage and restart protection.
- > Four adjustable miter angles with positive stops at 0°, 15°, 30° and 45° degrees in both left and right positions.
- > Accessories such as chip screen, sliding shoe for machining sensitive surfaces.
- > Conventional T-shank saw blade holder.
- > Comprehensive accessory portfolio such as saw blades for metal, wood, plastic, etc.
- > Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- > Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.

### Supplied

- ✓ 1 x 4 mm socket head wrench
- ✓ 1 x plastic sliding shoe
- ✓ 1 anti-chipping protector
- ✓ 1 x extraction adapter

## Technical data

### GENERAL TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Strokes	700 - 3,000 rpm
Tool Holder	T-shank (single-cam shank)
wood	150 mm
Stroke of blade	26 mm
Width	79 mm
Height	174 mm
Length	250 mm
Steel up to 400 N/mm <sup>2</sup>	12 mm
Non-ferrous metals up to 250 N/mm <sup>2</sup>	24 mm
Dimensions of base plate	156 x 73 mm
Weight without storage battery	2.10 kg

### VIBRATION AND NOISE EMISSION VALUES

Sound pressure level LpA	88,4 dB
Uncertainty of measured value KpA	5 dB
Sound power level LWA	96,4 dB
Uncertainty of measured value KWA	0 dB
Sound peak value LpCpeak	106,2 dB
Uncertainty of measured value KpCpeak	5 dB
Vibration value 1 dhv 3-way	7,4 m/s <sup>2</sup>
Vibration value 2 dhv 3-way	7,1 m/s <sup>2</sup>
Uncertainty of measured value Ka	1,5 m/s <sup>2</sup>

## Examples of use

